GENERAL ATOMICS
ELECTRONIC SYSTEMS

高壓保險絲
High Voltage Fuses

Specifications

Part Number	Rated Pulsed Current amps @ 1.5 msec	Rated DC Carrying Current amps	Cold Resistance @ 20°C milli-ohms	Hot Resistance @ 250°C milli-ohms	Rated Fuse Carrying Action A^2sec	Total Fuse Let-Through Action A^2sec	Element DC Fusing Current amps
94019	1000	25	74	145	1500	6300	47
94020	1500	30	51	102	3400	14,000	63
94021	2000	35	37	71	6000	26,000	80
94023	3000	43	25	48	14,000	57,000	109
94024	3500	45	22	44	18,000	72,000	119
94025	4000	49	19	36	24,000	100,000	134
94026	4500	52	17	33	30,000	130,000	145
94027	5000	54	15	31	38,000	150,000	156
94028	5500	56	14	28	45,000	180,000	167
94029	6000	59	13	25	54,000	220,000	179

244 新北市林口區仁愛路二段309號10樓
Tel：886-2-2608-8096（台北）/ Tel：86-21-6248-3333（上海）/ Fax：886-2-2608-8092
E-mail：sales@rapi-tech.com.tw www.rapi-tech.com