光源
Light Source

Spectral Products

ASB-XE-175 氙燈

ASB - XE - 175EX and ASB - XE - 175

Features

- High Color Temperature (5600ºK)
- CERMAX® Collimated Xenon Lamp
- Brightness Control (0-100%)
- Portable and light Weight
- CERMAX® Collimated Xenon Lamp
- Cool White light with the UV/IR Suppressed ASB-XE-175.

Specifications

Lamp	
Type	CERMAX®LX175BF
Power	200 Watts (maximum)
Color Temp	5600°K
Current	150-200W
Average Life	Typically 1000 hours (500 hours minumum)
Voltage	12-17V (14V nominal)
Trigger voltage	25 Kilivolts
Boost Voltage	140-200 Volts
Current Leakage	<300mA
Weight	7.5lbs. (3.4kg)
Input Line	95-136VAC, 50/60Hz (only)
Input Current	3.5 amp.
Environment	
Operating	+6 to +45 ° C
Storage	-40 to +70 ° C
Front Panel	Brightness Control (0-100%) Output Aperture
Side Panel	Main Power (On/Off) Line Cord Jack (IEC 320) (US to IEC Line Cord Included) Fuse Holder – MDL-5
Caution	Damage to glass or fused silica Fiber optic lightguides can occur due to high temperatures Associated with Xenon Lamps. Use our liquid light guides (order separately).
Order Information	
ASB-XE-175EX	Extended Xenon Source (200-2200nm)
ASB-XE-175BF	Ozone Blocking Xenon Source (320-750nm)
ASB-XE-175BFEX	ExtendedOzone Blocking Xenon (320-2200nm)
RB-175-BUV	Replacement Extended bulb
RB-175-BF	Replacement Ozone blocking bulb
AF5000-5000111DUV10S	Liquid Light Guide (220-600nm)
AF5000-5000111UV-VIS10S	Liquid Light Guide (300-650nm)
AF5000-5000111VIS10S	Liquid Light Guide (340-800nm)
AF5000-5000111VIS-IR10S	Liquid Light Guide (420-2000nm)

方全有限公司
Rapitech Enterprise Co.,Ltd.
244 新北市林口區仁愛路二段309號10樓
Tel : 886-2-2608-8096(台北) / Tel : 86-21-6248-3333(上海) / Fax : 886-2-2608-8092
E-mail : sales@rapi-tech.com.tw www.rapi-tech.com