# 光源
# Light Source

SP Spectral Products



## ASC-DC 可攜式校正光源
## Protable Wavelength Calibration Source


### Features

- Argon enhanced Mercury protable calibration lamp
- Highly repeatable wavelength, Linewidth, and intensity calibration standard
- Easily mounts to SP monochromaters and spectrographs
- Couples to SP AF series coupler for fiber optic output
- Convenient Battery with AD adapter for use in the field


### Specifications

| | |
|---|---|
| Lamp | Atomic emmission lamps with double bore fused silica tubing |
| Housing | Black anodized Aluminum |
| Dimensions | 4.125” x 1.25” x 0.875” (H x W x D) |
| AD Power | Wall transformer, 120VAC, 50/60 Hz to 9 VDC |
| Battery | 9V |
| Battery Life | 25-45 minutes On-time |
| Options | AF series fiber optic couplers |
| **Ordering information** | |
| ASC-HGAR-DC | Argon enhanced Mercury Spectral Calibration Lamp |

### Hg spectral calibration data




### Ar spectral calibration data




方全有限公司
Rapitech Enterprise Co.,Ltd.
244 新北市林口區仁愛路二段309號10樓
Tel：886-2-2608-8096（台北）/ Tel：86-21-6248-3333（上海）/ Fax：886-2-2608-8092
E-mail：sales@rapi-tech.com.tw www.rapi-tech.com